

CJX2-K Mini Contactor

| AC Contactor | | CJX2-K12 | |
|---|--|--|------|
| Type | | | |
| Rated Power kW/HP(AC-3) IEC60947- 4 - 1 GB14048.4 | 200-240V | 3/4 | |
| | 380-440V | 5.5/7.5 | |
| | 500-550V | 4/5.5 | |
| | 660-690V | 4/5.5 | |
| Rated Power kW/HP(AC-3) IEC60947- 4 - 1 GB14048.4 | 200-240V | 12 | |
| | 380-440V | 12 | |
| | 500-550V | 7 | |
| | 660-690V | 5 | |
| Conventional Thermal Current Ith:(A) | | 20 | |
| Rated Insulated Voltage Ui:(V) | | 690 | |
| Auxiliary Contact AC-15 | Contact Arrangement | Standard | 1NO |
| | | Special | ---- |
| | Rated Power kW/HP(AC-15) IEC60947- 4 - 1 GB14048.4 | 200-240V | 1.6 |
| | | 380-440V | 0.95 |
| Conventional Thermal Current Ith:(A) | | 16 | |
| (AC-3) Electrical Life (Million Times) | | 1 | |
| (AC-3) Mechanical Life (Million Times) | | 8 | |
| Connection Circuits | | | |
| Coil Voltage (V) | AC 50Hz/60Hz | 110, 220/230 | |
| Acting Range | Attraction (Hot) | (85% ~ 110%) Us ; +40 °C | |
| | Release (Cold) | AC:(20% ~ 75%) Us ; -5 °C" | |
| Installation | | 35mm DIN Rail or screw (M4) | |
| Connection | Main Contact | Screw (M3) Wire 1-4 mm ² | |
| | Aux. Contact / Coil | Screw (M3) line-pressed terminal | |